

MATERIAL SAFETY DATA SHEET

Page 1 of 2
Updated 04/10/2007

PRODUCT: Rockcote EcoStyle Ceiling White

Not classified as hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company Details Rockcote Enterprises Pty Ltd (ABN 42 066 227 174)
Address 18 Machinery Road Yandina Qld 4561
Telephone/Fax **Tel** (07) 5446 7737 **Fax** (07) 5446 8303
Emergency Telephone 0438 798 209 (Technical Manager)
Other Information Note: For the most up-to-date information for this data sheet, please refer to the Rockcote website www.rockcote.com.au
The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in this material safety data sheet do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein.

IDENTIFICATION

Product Name Rockcote EcoStyle Ceiling White
Other Names None Listed
Product Code None Listed
UN No: None allocated
Hazchem: None allocated
D.G. Class: None allocated
Pack. Grp.: None allocated
Product Type: Acrylic Emulsion Paint
Major Ingredients: Water based acrylic polymer inert pigments.
Poisons Schedule Not scheduled
Product Use Ceiling Finish

PHYSICAL PROPERTIES

Appearance: Pigmented Paint
Odour: Slight Acrylic
Viscosity: 11000 cps (Brookfield)
pH: 8.5 - 9.5
Specific Gravity: 1.5
Flash Point: Non Combustible
Solubility in Water: Dilutable

OTHER PROPERTIES

Volatile Component N/A
Auto ignition Temp. N/A
Stability Stable

MAJOR INGREDIENTS

| Name: | Quantity |
|--------------------|-----------------|
| Inert Pigments | 45-55% |
| Polymer Dispersion | 5-15% |
| Additives | <10% |

FIRST AID INFORMATION

| | |
|----------------------|---|
| Inhalation: | Move subject to fresh air. |
| Skin Contact: | Wash affected areas thoroughly with soap & water. Consult a physician if irritation persists. |
| Eye Contact: | Flush eyes with large amount of water for at least 15 minutes, holding the eye lids apart. Consult a physician if irritation persists. |
| Ingestion: | If swallowed drink at least 2 glasses of water. Consult a physician. |

PERSONAL PROTECTION

Use only in well ventilated areas. Wear protective clothing to minimise skin contact. Where splatter is likely, wear goggles.

FLAMMABILITY

Fire Hazards Material is non flammable in wet but combustible in dry state.

SAFE HANDLING INFORMATION**Storage and Transport**

| | | | |
|------------------|---|-----------|---------------------|
| STORAGE | Store in a cool dry place and out of the weather. | | |
| TRANSPORT | Road and Rail Transport (ACTDG): | Class NIL | |
| | IATA Classification: | Class NIL | Packaging Group NIL |

FIRE FIGHTING INFORMATION

| | |
|-------------------------------|--|
| Extinguishing Agents: | Use extinguishing media appropriate for surrounding fire. |
| Storage Requirements: | Store out of direct sunlight. Store above 4°C & below 50°C. |
| Spills & Clean Up: | Contain spills with sand or earth. Remove to suitable container for disposal. Wash area and equipment with water. Do not allow cleaning water and/or runoffs to enter sewers, storm water or open bodies of water. |

.....END OF MSDS.....

This MSDS has been developed according to Worksafe Australia / NOHSC guidelines.