

ROCKCOTE EcoStyle - Technical information at a glance for Specifiers

Product	<i>EcoStyle Sealer/ Undercoat</i>	<i>EcoStyle Ceiling White</i>	<i>EcoStyle Low Sheen</i>	<i>EcoStyle Flat</i>	<i>EcoStyle Satin</i>	<i>EcoStyle Gloss</i>
Recommended Interior / Exterior	Interior/ Exterior^	Interior	Interior/ Exterior^	Interior	Interior/ Exterior^	Interior/ Exterior^
Recommended Coverage (m ² /L)*	7-14	14	14	14	16	16
Volume solids (%)	37	42	39	39	37	35
Recoat Time (Hrs) (55% Relative Humidity, 25°C)	2	2	2	2	4	5
Touch Dry (Minutes) (55% Relative Humidity, 25°C)	30	30	30	30	45	45
Specific Gravity	1.26	1.52	1.33	1.35	1.29	1.25
Gloss level (60DH) (0=Most Flat, 100= Highest Gloss)	9	<1.1 (85°)	5	3.5	25	80
AS/NZS 2311:200 Gloss specification (0= Most Flat, 100= Highest Gloss)	n/a	Flat <5	Low Sheen 5-20	Flat <5	Semi Gloss 20-50	Gloss 50-85
%VOC by weight	0.0 - 0.03	0.0 - 0.01	0.0 - 0.04	0.0 - 0.04	0.0 - 0.18	0.00 - 0.20
VOC # gm/L	0.0 - 0.4	0.0 - 0.1	0.0 - 0.6	0.0 - 0.6	0.0 - 2.4	0.0 - 2.5

^ In warm, dry conditions, or in direct exposure to the sun, addition of Floetrol® may be necessary for exterior use to maintain a wet edge.

* Coverage depends on substrate porosity and texture and wastage factors.

EcoStyle Paints comply with the VOC limits in APAS specification 0215 "Interior Latex Paint, Low Odour, Low VOC"

- All paints are low odour and dry paint films are all odourless.
- All EcoStyle paints have Sensitive Choice Approval by The Asthma Council of Australia for interior & exterior use and are classed as Zero VOC. This approval is valid when used untinted or when tinted using the ROCKCOTE Tinting System. This gives EcoStyle paints the edge over other commercially available products which are only classified as Zero VOC when used untinted. Refer to the document, ROCKCOTE VOC Challenge.
- All EcoStyle paints are certified under the Australian Ecolabelling Program (Good Environmental Choice Australia) "GREENSTAR" when untinted or tinted with the ROCKCOTE Tinting System.



green building council australia
MEMBER 2009-2010

