

MATERIAL SAFETY DATA SHEET

Page 1 of 2
Updated 12/12/2006

PRODUCT: **Rockcote Solprime**

Classified as hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company Details Rockcote Enterprises Pty Ltd (ABN 42 066 227 174)
Address 18 Machinery Road Yandina Qld 4561
Telephone/Fax **Tel** (07) 5446 7737 **Fax** (07) 5446 8303
Emergency Telephone 0417 694 695 (Chemist)
Other Information Note: For the most up-to-date information for this data sheet, please refer to the Rockcote website www.rockcote.com.au
The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in this material safety data sheet do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein.

IDENTIFICATION

Product Name Rockcote Solprime
Other Names None Listed
Product Code Xn (Harmful)
UN No: 1300
Hazchem: 3[Y]
D.G. Class: 3
Pack. Grp.: III
Product Type: Paint - Flammable
Major Ingredients: Aromatic Hydrocarbon
Acrylate/Methacrylate and Turpentine
Poisons Schedule S5
Product Use Roll-on, Brush-on, or spray-on Paint

PHYSICAL PROPERTIES

Appearance: Colourless Liquid
Odour: Hydrocarbon
Viscosity: Thin, mobile liquid
pH: N/A
Specific Gravity: 0.85
Flash Point: 36°C
Solubility in Water: Insoluble

OTHER PROPERTIES

Volatile Component 50%
Auto ignition Temp. N/Avail
Stability Stable

HEALTH HAZARD INFORMATION

Primary Routes of Exposure:

Inhalation: (**Severe Exposure**) Inhalation of vapour can cause headache, nausea, irritation of nose, throat & lungs. Prolonged exposure can cause dizziness and/or unconsciousness.

Skin Contact: Burning sensation on skin, also drying and cracking.
Solprime is absorbed slowly through the skin.

Eye Contact: Vapour can irritate eyes.
Liquid can cause severe irritation, swelling and corneal burns.

Ingestion: Burning sensation in stomach, damage to lining of stomach and intestines. Severe lung damage if aspirated.

FIRST AID INFORMATION

Inhalation:	Move subject to fresh air. If breathing has stopped begin artificial respiration and obtain medical attention immediately.
Skin Contact:	Immediately wash affected areas thoroughly with soap & water. Remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice.
Eye Contact:	Flush eyes with large amount of water for at least 15 minutes, holding the eye lids apart. Consult a physician if irritation persists.
Ingestion:	Rinse mouth with water. Give water to drink. DO NOT INDUCE VOMITING. Seek medical assistance.
Toxicity Data: (Typical)	Oral LD 50 (Rat): > 2000 mg/kg Dermal LD 50 (Rabbit): > 2000 mg/kg

PERSONAL PROTECTION

Use only in well ventilated areas. Wear protective clothing to minimise skin contact. Where splatter is likely, wear goggles.

FLAMMABILITY

Fire Hazards Material is **flammable (Class 3)**

SAFE HANDLING INFORMATION**Storage and Transport**

STORAGE Store in a cool place and out of direct sunlight. Store away from sources of heat or ignition and in a well ventilated area. Keep containers sealed when not in use.

TRANSPORT Road and Rail Transport (ACTDG): Class 3
IATA Classification: 1866 Packaging Group III

FIRE FIGHTING INFORMATION

Extinguishing Agents: Foam, dry powder, or carbon dioxide.

Unusual Hazards: Material is **FLAMMABLE** and vapour is heavier than air, and can collect in low lying areas and tanks.

Spills & Clean Up: Contain spills with sand or earth. Remove to suitable container for disposal. Wash area and equipment with water. Do not allow cleaning water and/or runoffs to enter sewers, storm water or open bodies of water.

.....**END OF MSDS**.....

This MSDS has been developed according to Worksafe Australia / NOHSC guidelines.