

ROCKCOTE Wet Edge Extender

ROCKCOTE Wet Edge Extender is an additive for use in all ROCKCOTE water-borne paints and textures, other than ROCKCOTE EcoStyle products.

PERFORMANCE & PROPERTIES

ROCKCOTE Wet Edge Extender works by slowing down the drying process of water borne coatings thus allowing more time for workability and finishing. It is principally used when ambient conditions are hot and/or dry.

Limitations

- Not suitable for use in ROCKCOTE EcoStyle products
- Not recommended for use when the temperature is 20°C or lower and/or the ambient relative humidity is 65% or higher during drying.
- Use the minimum amount required to achieve desired results. Particularly use sparingly in trowel on type coatings (see addition rates below). ROCKCOTE Wet Edge Extender may adversely affect the application properties of trowel-on coatings or stipple effects in Armours or roll on textures if too much is added.*
- Use sparingly if rain or high humidity conditions are imminent.

APPLICATION

The base texture coat or substrate must be suitably dry with a moisture reading of less than 15% WME and free from mould, loose particles, grime or other surface contaminants.

Add to the product and mix in with a mixing paddle or mechanical mixer. No activation time is necessary.

For the best results coatings used with the addition of ROCKCOTE Wet Edge Extender should be applied as evenly as possible and excessive film builds should be avoided. Special care should be taken on building corners, join lines at scaffold drops and cut in areas where an excessive build up of product may occur. See ROCKCOTE Technical Article on Cutting In and Avoiding "Picture Framing".

Flammability	Non Flammable. See MSDS
Clean Up	Clean with water immediately after use
Addition rates	ROCKCOTE Armour products: Up to 40ml per 1 litre of product* Roll-on Textures: Up to 30ml per 1 litre of product* ROCKCOTE Trowel-On Textures: Up to 15ml per 1 litre of product*
Pack Size	4L & 15L plastic pails

STORAGE, SAFETY & HANDLING

- Refer to the MSDS for ROCKCOTE Wet Edge Extender
- Pails should not be stacked more than three high during transportation and should be stored out of direct sunlight and above 4°C.
- Wear protective clothing to minimise skin contact and wear goggles where spatter is likely
- Avoid inhalation of mist or vapour and prolonged skin contact and particularly eye contact.
- If skin contact occurs, flush thoroughly with clean water.
- In the case of ROCKCOTE Wet Edge Extender, if ingestion occurs, drink at least two glasses of water and consult a doctor.
- Where spills occur, soak up liquid spillage with sand or sawdust before disposal.
- Clean up equipment and area with water. Do not permit run-off to sewer, storm water or open bodies of water.

Indemnity

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice.