

# Technical Data Sheet

## ROCKCOTE PREMIUM CEILING WHITE

**Effective From** 13 Nov, 2017

ROCKCOTE Premium Ceiling White is a premium ceiling white paint formulated for interior use. This low VOC (Volatile Organic Compound) formulation is a water-borne ceiling paint, specifically designed for the professional painter. ROCKCOTE Premium Ceiling White does not contain any crystalline silica which is harmful to human health and can lead to Silicosis. Formulated from high grade components, this emulsion based product provides maximum adhesion to most surfaces and dries to an ultra flat finish with excellent opacity.

### Features

- Safe/low odour.
- Low spatter.
- Easy touch up.
- High flow.
- Excellent workability.
- High opacity.

### Benefits

- Quick application.
- Low VOC.
- Great coverage and hiding capacity.

### Uses

- ROCKCOTE Premium Ceiling White is for use on ceilings only.

**Colours and Gloss** ROCKCOTE Premium Ceiling White can be tinted to off-white shades or hues to create a continuity or "flow" between wall and ceiling colours. However, it has not been formulated to exactly match a ROCKCOTE white base.

**Sheen Level** Ultra flat <1.

**Coverage Rate** 16m<sup>2</sup>/ltr  
Coverage rates may vary according to substrate and preparation. ROCKCOTE Premium Ceiling White is usually applied at the rate of approximately 16 square metres per litre.

**Application Method** Spray, Roller or Brush

**Dry Film Build**

**Wet Film Build**

### Typical Data at 25°C and 50% Relative Humidity

**Drying Time** 2 hours

**Touch Dry** 30 minutes

**Dry to Recoat** 2 hours

**Usual No Coats** 2

**Clean Up** Water

**Packaging Sizes** Trade 20L  15L  10L  4L  1L

**Volume Solids**

**Thinning** 5% Water

**Elongation Rate**

**Crack Bridging**

**Abrasion Resistance**

**Moisture Control**

**Water Resistance**

# Technical Data Sheet

## ROCKCOTE PREMIUM CEILING WHITE

<b>Effective From</b>	13 Nov, 2017
-----------------------	--------------

### Substrate Conditions

- Ensure the surface is free from loose material, clean, dry and free from oil and grease. Sand any non-porous surfaces such as glossy painted areas. Patch and fill holes and cracks with suitable plaster patching compound and sand back to give an even finish before painting. Do not sand the paper surface of plasterboard. Clean any mould, mildew or fungi. ROCKCOTE Premium Ceiling White does not support the growth of mould, mildew and fungi.
- For previously painted: A sealer is not normally required.
- Plasterboard (paper covered): ROCKCOTE recommends a coat of ROCKCOTE EcoStyle Primer prior to 2 coats of ROCKCOTE Premium Ceiling White.
- Cement and cement sheet: If required apply 1 coat ROCKCOTE Primer then 2 coats of ROCKCOTE Premium Ceiling White.
- Timber and hardboard: Apply 1 coat of ROCKCOTE EcoStyle Sealer/Undercoat then 2 coats of ROCKCOTE Premium Ceiling White.
- Timbers that are rich in tannins: A stain resistant primer should be used.

### Application

- If using multiple pails, contents must be boxed together to ensure colour consistency.
- Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions. See ROCKCOTE's Technical Article on Cutting In and avoiding "Picture Framing".
- For airless spray use 0.013 - 0.017 inch spray tips and adjust the flow rate and fan width to minimise water required to thin.
- Can be thinned up to 5% volume with water.

### Precautions and Limitations

- ROCKCOTE Premium Ceiling White should not be applied in temperatures below 5°C or above 35°C.
- ROCKCOTE Premium Ceiling White is not suitable for areas of continual damp or areas submerged in water.
- Not for use over unsealed hardwood.

### Transport and Storage

- Store in a cool dark place.
- Keep pail sealed.
- Do not stack more than 3 pails high.
- Do not double stack pallets.
- Top load only.

### Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

# Technical Data Sheet



## ROCKCOTE PREMIUM CEILING WHITE

<b>Effective From</b>	13 Nov, 2017
-----------------------	--------------

### Safety Data

Refer ROCKCOTE Premium Ceiling White SDS

### Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.