

TECHNICAL DATA SHEET

ROCKCOTE MARRAKESH

Last Updated July 2015

Description	ROCKCOTE Marrakesh is a fine-grained lime plaster that can be used both interior and exterior. It can be used for walls, shower walls and splashbacks in wet areas (bathrooms, showers, laundries and toilets) but is not recommended for areas where water pools such as floors, shower floors bath tubs or hand basins as successful application requires an exceptional level of skill and experience.				
	<table><tr><td>Features</td><td>Benefits</td></tr><tr><td><ul style="list-style-type: none">•Natural lime-based product•Smooth, seamless, stone look•Resistant to moisture and humidity•Low embodied energy</td><td><ul style="list-style-type: none">•Extremely durable•Create a seamless finish•Helps improve internal air quality•Low to no odour and no residual off-gassing</td></tr></table>	Features	Benefits	<ul style="list-style-type: none">•Natural lime-based product•Smooth, seamless, stone look•Resistant to moisture and humidity•Low embodied energy	<ul style="list-style-type: none">•Extremely durable•Create a seamless finish•Helps improve internal air quality•Low to no odour and no residual off-gassing
Features	Benefits				
<ul style="list-style-type: none">•Natural lime-based product•Smooth, seamless, stone look•Resistant to moisture and humidity•Low embodied energy	<ul style="list-style-type: none">•Extremely durable•Create a seamless finish•Helps improve internal air quality•Low to no odour and no residual off-gassing				
Uses	<ul style="list-style-type: none">•Suitable for interior and exterior use•Create a traditional Tadelakt of Moroccan plaster look.•Can also be finished to a traditional flat lime plaster or for a contemporary look can be used to achieve a glass face marble plaster.•Create a seamless bathroom where the smooth curve of one element flows into another, evoking a sense of ease and continuity not felt in a standard bathroom.•Marrakesh allows the artisan to create an individual work of art on any wall or in any room within the home. Many different styles of finish can be achieved using different trowels, floats, sponges and finishing techniques				
Colours and Gloss	Off-white to white colour. Can be tinted to a wide range of colours using alkali resistant oxides. ROCKCOTE recommends not exceeding 4% of product weight in oxide				
Sheen Level	From a flat/matt finish up to a polished lustre or glass finish				
Typical Data at 25 °C and 50% Relative Humidity					
Volume Solids	100%				
Coverage Rate	Approximately 4 square metres per 16kg bag at 2mm thickness.				
Film Build	2 - 3mm (as a finish coat).				
Dry to Recoat	30 minutes to one hour				
Curing Time	28 days				
Pot Life	4 hrs				
Usual No Coats	1 coat at 2-3mm for smooth, trowel or sponge finish; 2 coats at 2mm for glass or lustre polished finish				
Packaging Sizes	16 Kg Bags				
Clean Up	Water				
Substrate Conditions	Substrate must be installed as per manufacturer's specifications. Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination. Any base coats should be fully cured. Substrates must not contain more than 15% moisture prior to the application of the ROCKCOTE system. For full details on application for each substrate, refer to the ROCKCOTE Natural Materials Systems Guide.				
Flooring Installation	N/A				
Mixing	ROCKCOTE Marrakesh is a hydraulic lime and DOES NOT need to be soaked. Add 4.8 to 5.2 litres of clean fresh water to a clean bucket and slowly add ROCKCOTE Marrakesh while mixing. Mixture will be quite wet directly after mixing, this is normal and after 15 -20 minutes of standing, will thicken. Remix to a workable consistency.				
Application	The application of ROCKCOTE Natural Materials is a highly skilled process that requires experience working with natural building products and systems. It is the responsibility of the applicator to select the right product and system for the job and ensure correct installation and application according to the above and other relevant criteria. We recommend that project				

TECHNICAL DATA SHEET

ROCKCOTE MARRAKESH

Last Updated July 2015

managers and clients appoint only applicators experienced in the relevant ROCKCOTE Natural Material in situations and with desired aesthetics similar to the project at hand

Safety Data

Refer to ROCKCOTE Marrakesh SDS.

Precautions and Limitations

- ROCKCOTE Marrakesh is highly alkaline due to the inclusion of hydrated lime. Please ensure adequate PPE is used when mixing and applying.
- Many substrates can be coated with ROCKCOTE Marrakesh but the high alkalinity may affect the underlying coating. Always contact ROCKCOTE or refer to the ROCKCOTE Natural Materials Systems Guide before using.
- ROCKCOTE Marrakesh should not be applied in temperatures below 5 degrees C or above 35 degrees C.
- ROCKCOTE Marrakesh is not suitable for areas of continual damp or areas submerged in water.
- ROCKCOTE Marrakesh is suitable for walls, shower walls and splashbacks in wet areas but not recommended for areas where water pools such as floors, shower floors, bath tubs or hand basins. ROCKCOTE recommends that this product be applied by a licensed tradesperson who has extensive experience in applying these products for similar applications to your particular project. The success of each project requires the tradesperson to have a thorough technical knowledge of appropriate building design, substrate conditions and their client expectations to determine if Marrakesh or Venetian Plaster are fit for the purpose expected for your particular project.

Transport and Storage

- Store in a cool, dark place
- Keep pail sealed

Disposal

- Dispose of in accordance with local council regulations

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.