

Technical Data Sheet

ROCKCOTE MASONRY PRIMER HI OP

Effective From 15 Nov, 2017

ROCKCOTE Masonry Primer Hi Op is a high performance full acrylic primer for use over many different substrates. ROCKCOTE Masonry Primer Hi Op provides a low suction substrate that will increase the lifespan of subsequent paint coatings. ROCKCOTE Masonry Primer Hi Op is ideal as a primer for use with ROCKCOTE high performance membranes and colored textures.

Features

- Alkali resistant.
- Easy to use.
- Highly adhesive.

Benefits

- Reduces suction.
- High opacity (light base)

Uses

- Reduces suction on porous and high suction substrates such as A.A.C, fibre cement sheeting, render and masonry.
- Ideal for priming or sealing substrates prior to the application ROCKCOTE high performance membranes and roll on texture systems.
- Can be used interior and exterior.

Colours and Gloss

- Can be tinted to a wide range of colours.

Sheen Level Low Sheen

Coverage Rate 6m²/ltr
Approximately 6 square metres per litre, Figures are a guide only. Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Application Method Brush or Long Nap Roller

Dry Film Build

Wet Film Build

Typical Data at 25°C and 50% Relative Humidity

Drying Time 2 hours

Touch Dry 1 hours

Dry to Recoat 2 hours

Usual No Coats 1

Clean Up Water

Packaging Sizes Trade 20L 15L 10L 4L 1L

Volume Solids

Thinning 5%

Elongation Rate

Crack Bridging

Abrasion Resistance Excellent

Moisture Control

Water Resistance

Technical Data Sheet

ROCKCOTE MASONRY PRIMER HI OP

Effective From	15 Nov, 2017
-----------------------	--------------

Substrate Conditions

- Surfaces should be clean, dry and free from loose or crumbling material, oil or from release agents.
- Care should be taken to keep ROCKCOTE Masonry Primer Hi Op off windows and adjacent surfaces that are not to be coated, as they can be very difficult to remove once allowed to dry.
- All substrates must be installed as per manufacturers' specifications prior to application.
- Not suitable for areas that will be submerged in water or subjected to continual moisture.

Application

- If using multiple pails on a wall, box drums prior to use.
- The application of this product is a specialist procedure which should be carried out by a skilled and experienced applicator.
- It is important to maintain a wet edge when applying to avoid tracking and picture framing. (See ROCKCOTE's article on Picture Framing.)
- Must be applied evenly and consistently to provide colour consistency and opacity for top coats.
- Can be applied with a quality brush or 15-20mm long nap sheepskin roller.
- For tilt up precast concrete panels, ROCKCOTE Solprime must be applied prior to application.

Precautions and Limitations

- Should not be applied in air and surface temperatures below 5°C or above 35°C.
- Should not be applied over glossy silicone based paints or sealants.
- ROCKCOTE Primers should only be used over sound clean substrates, and are not suitable for areas that will be submerged in water or subjected to continual moisture.
- ROCKCOTE Masonry Primer Hi Op must only be used on substrates with a moisture level of less than 15% WME.
- ROCKCOTE Primers are not suitable for use direct to substrates below damp proof installments.

Transport and Storage

- Store in a cool dark place.
- Keep pail sealed.
- Do not stack over 3 high.

Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

Technical Data Sheet



ROCKCOTE MASONRY PRIMER HI OP

Effective From	15 Nov, 2017
-----------------------	--------------

Safety Data

Refer to ROCKCOTE Masonry Primer Hi Op SDS

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.