

TECHNICAL DATA SHEET

ROCKCOTE REPEL

Last Updated July 2016

Description	ROCKCOTE Repel is a clear, low build finish developed to provide added resistance against water ingress, mould and grime pick up over the complete range of ROCKCOTE finishes				
	<table><tr><td>Features</td><td>Benefits</td></tr><tr><td><ul style="list-style-type: none">• *10 year warranty• Water based• Ease of use• Vapour permeable</td><td><ul style="list-style-type: none">• High water resistance• Long term exterior protection• Mould resistant• Scuff resistant• Easy to use• Easy to maintain</td></tr></table>	Features	Benefits	<ul style="list-style-type: none">• *10 year warranty• Water based• Ease of use• Vapour permeable	<ul style="list-style-type: none">• High water resistance• Long term exterior protection• Mould resistant• Scuff resistant• Easy to use• Easy to maintain
Features	Benefits				
<ul style="list-style-type: none">• *10 year warranty• Water based• Ease of use• Vapour permeable	<ul style="list-style-type: none">• High water resistance• Long term exterior protection• Mould resistant• Scuff resistant• Easy to use• Easy to maintain				
Uses	<ul style="list-style-type: none">• Provides a highly water repellent and mould resistant surface when applied over ROCKCOTE Texture Coatings• Can be used as a top coat over ROCKCOTE Coloured Renders and specialist products to provide extra protection• Can be used interior and exterior				
Colours and Gloss	Dries to a clear finish				
Sheen Level	Low Sheen				
Typical Data at 25 °C and 50% Relative Humidity					
Volume Solids	10%				
Coverage Rate	Coverage Rate: Approximately 4 to 8m ² /ltr				
Drying Time	4 hours				
Touch Dry	1.5 hours				
Dry to Recoat	4 hours				
Moisture Control	Excellent				
Abrasion Resistance	Excellent				
Usual No Coats	1				
Packaging Sizes	20 ltr Drum				
Clean Up	Water				
Substrate Conditions	<ul style="list-style-type: none">• Must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants• All substrates must be installed as per manufacturers' specifications prior to application• Do not apply if air and surface temperatures are below 5°C or above 35°C				
Flooring Installation	N/A				
Mixing	N/A				
Application	<ul style="list-style-type: none">• Should be applied as evenly as possible by brush, roller or spray equipment, ensuring complete coverage whilst maintaining a wet edge• Alternatively Rockcote Repel can be sprayed on and brushed or broomed in• After application with a medium nap roller it is important to tip off the product to ensure an even appearance and drying• Care should be taken not to apply too much product on cut-in areas• An 80mm wide roller of medium nap pile should be used for cutting in• See ROCKCOTE's Technical Article on "Cutting In and avoiding picture framing"				
Safety Data	Refer to ROCKCOTE Repel SDS				
Precautions and Limitations	<ul style="list-style-type: none">• Should not be applied in air and surface temperatures below 5°C or above 35°C• Should not be applied over glossy silicone based paints or sealants				

TECHNICAL DATA SHEET

ROCKCOTE REPEL

Last Updated July 2016

- Not recommended for floors
- Not suitable for areas totally immersed in water
- Unsuitable for use as a clear finish over exterior timber

Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 2 high

Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

* WHEN USED AS PART OF A FULL ROCKCOTE SYSTEM.