

TECHNICAL DATA SHEET

ROCKCOTE RUST INHIBITING PRIMER

Last Updated July 2016

Description ROCKCOTE Rust Inhibiting Primer is a fast-drying, white-pigmented acrylic latex primer. It is designed to prime, seal and block out most stains on many different types of exterior and interior surfaces, including oil, acrylic or latex finish paints. The unique formulation combines fast dry, low odour and easy clean up properties with outstanding performance. This makes it particularly valuable in many institutional, commercial and industrial applications

Features

- 10 year warranty*
- Water based
- Alkali resistant
- Vapour permeable
- Blocks most stains
- Durable

Benefits

- Water repellent
- Mould resistant
- Low odour
- Reduces suction

Uses • Suitable for application over properly prepared surfaces such as gutters, downpipes, vents, nail heads, iron railings and decorative metal work
• Blocks out stains such as water, grease, rust, smoke, redwood, creosote and asphalt stains
• Provides excellent adhesion for subsequent coatings

Colours and Gloss ROCKCOTE Rust Inhibiting Primer is available in white base. It is not recommended that tints are used on this product as it may affect its stain blocking properties

Sheen Level Low Sheen

Typical Data at 25 °C and 50% Relative Humidity

Volume Solids 50%

Thinning Not recommended

Coverage Rate Approximately 10 square metres per litre, Figures are a guide only. Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Film Build Dry film build: 35 microns Wet film build: 70 microns

Drying Time 1.5 hours

Touch Dry 45 minutes

Dry to Recoat 1.5 hours

Usual No Coats 1

Packaging Sizes 15 Ltr, 4 Ltr & 1 Ltr pails

Clean Up Clean with water immediately after use. Recently dried material can be removed with methylated spirits.

Substrate Conditions

- Surfaces must be clean, dry and free of scaling paint, loose wallpaper and wallpaper paste
- Remove any wax with mineral spirits
- If surface is extremely dirty or chalky, wash with stiff brush and water
- Test all old painted or varnished surfaces for adhesion by making an X with a razor knife and placing a section of Scotch® tape over, pressing down with thumb. After 30 seconds, yank the tape off (do not pull, but yank the tape). If old paint or varnish comes off on the tape, the paint should be removed. Never paint over any painted surface that fails this test
- Galvanised iron (new): Clean with scouring pad and sugar soap solution. Rinse off thoroughly
- Galvanised iron (old): Remove rust by wire brush or scraping. Clean with scouring pad and sugar soap solution. Rinse off thoroughly
- Steel/wrought iron (new): Wipe surface with mineral turpentine to remove all residual material. Allow to dry
- Steel/wrought iron (old): Remove rust by wire brush or scraping. Wipe surface with mineral turpentine to remove all residual material. Allow to dry

Flooring Installation N/A

Mixing N/A

TECHNICAL DATA SHEET

ROCKCOTE RUST INHIBITING PRIMER

Last Updated July 2016

Application	This product may be applied by brush, roller or sprayer. When brushing, use a good quality synthetic bristle brush, flow product on and brush out. For rolling, best results are achieved using a short nap roller. If using airless sprayer, do not thin. If using conventional air sprayer, spray at 50-60 psi. Do not apply below 5°C or above 35°C or in hot windy conditions
Safety Data	Refer ROCKCOTE Rust Inhibiting Primer SDS
Precautions and Limitations	<ul style="list-style-type: none">• Should not be applied in temperatures below 5°C or above 35°C• Not suitable for areas of continual damp or areas submerged in water• Not suitable for floors• Not suitable for flat rooftops
Transport and Storage	<ul style="list-style-type: none">• Store in a cool dark place• Keep pail sealed• Do not stack over 3 high
Disposal	<ul style="list-style-type: none">• Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal• Product must not be allowed to run into drains or open bodies of water• Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations• Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System
Disclaimer	<p>ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.</p> <p>* WHEN USED AS PART OF A FULL ROCKCOTE SYSTEM.</p>