

TECHNICAL DATA SHEET

ROCKCOTE SMOOTH SANDING PATCH

Last Updated January 2017

Description ROCKCOTE Smooth Sanding Patch is an ultra fine ready mixed, water based, easily sanded acrylic patching compound, showing negligible shrinkage in one application. It is designed for patching holes, form joints & minor imperfections in concrete or masonry walls. ROCKCOTE Smooth Sanding Patch can also be used to create a smooth finish over inconsistent substrates prior to painting.

Features

- *10 year warranty
- Easy to use
- Exhibits minimal shrinkage
- Excellent adhesion qualities

Benefits

- Tough
- Interior/Exterior* use

Uses

- Designed for patching off form concrete joints and minor imperfections
- Can be used over ROCKCOTE Patch & Prep on fibre cement sheeting joints for a finer finish
- Can be used as a top coat over ROCKCOTE Quick Render to provide a smooth flat finish
- Can be used interior and exterior

Colours and Gloss Not generally coloured, but can be tinted to a range of light to medium depth colours. *NB exact colour accuracy cannot be guaranteed, please allow for slight variation when making colour selection.

Sheen Level N/A

Typical Data at 25 °C and 50% Relative Humidity

Coverage Rate Approximately 15 square metres per 15 litre pail @ 1mm build

Film Build For best results, do not apply greater than 2mm wet film build. Use multiple coats for higher build.

Drying Time Dependent on temperature, humidity and film build.

Touch Dry Dependent on temperature, humidity and film build.

Dry to Recoat Dependent on temperature, humidity and film build.

Crack Bridging Good

Abrasion Resistance Excellent

Usual No Coats Suitable for multiple coat application.

Packaging Sizes 15 Ltr Pails

Clean Up Water

Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust and any other contaminants
- All substrates must be installed as per manufacturers' specifications prior to application

Flooring Installation N/A

Mixing N/A

Application

- Mix contents of pail before use
- For external applications 3 litres per 15ltr pail of lump free uncompressed cement powder must be added to this product
- For larger patching imperfections in concrete, wet down the wall and once the sheen has receded apply ROCKCOTE Patch & Prep or Skimcote to the area and flush off whilst damp then apply ROCKCOTE Smooth Sanding Patch once cured

Safety Data Refer ROCKCOTE Smooth Sanding Patch SDS

Precautions and Limitations

- Not for use on fibre cement joints as a taping compound
- Should not be applied in temperatures below 5°C or above 35°C
- Should not be applied over glossy silicone based paints or sealants

TECHNICAL DATA SHEET

ROCKCOTE SMOOTH SANDING PATCH

Last Updated January 2017

Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 3 high

Disposal

- Dispose of in accordance with local council regulations

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.
* WHEN USED AS PART OF A FULL ROCKCOTE SYSTEM.
