

Technical Data Sheet

ROCKCOTE SOFFIT STIPPLE COAT

Effective From 01 Jan, 2019

ROCKCOTE Soffit Stipple Coat is a 100% acrylic water based stipple finish for exterior concrete soffits and ceilings in multi-story buildings. Flexible and able to bridge cracks over 1mm in thickness, ROCKCOTE Soffit Stipple Coat delivers an attractive matt finish to hide imperfections with a uniform stippled texture.

Features

- Water based
- Excellent flexibility
- Vapour permeable
- Easy to maintain

Benefits

- Mould resistant
- Matt finish
- Easy to use
- Will bridge existing cracks of up to 1mm

Uses

- Designed specifically for creating a uniform stippled texture over pre cast and off form ceilings and soffits.
- Can be used interior and exterior.

Colours and Gloss

- Can be tinted to white base colours only

Sheen Level

Matt

Coverage Rate

2-3m²/ltr

Medium Stipple Profile: 2.0m²/ltr per coat

*Based on smooth substrate

Application Method

Long Nap Roller or stipple texture roller

Dry Film Build

160-250 µm depending on roller used

Wet Film Build

Medium Profile: 400-500 µm per coat

Typical Data at 25°C and 50% Relative Humidity

Drying Time 6-8 hours

Touch Dry 2 hours

Dry to Recoat 6-8 hours

Usual No Coats

2

Clean Up

Water

Packaging Sizes

Trade 20L 15L 10L 4L 1L

Volume Solids

50

Thinning

Up to 5%

Elongation Rate

Crack Bridging

8.9 times DFT (AS4548.5/F Static Test)

Abrasion Resistance

Excellent

Moisture Control

Excellent

Water Resistance

Excellent

Technical Data Sheet

ROCKCOTE SOFFIT STIPPLE COAT

Effective From	01 Jan, 2019
-----------------------	--------------

Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants and contain less than 15% Wood Moisture Equivalent (WME).
- Do not apply if air and surface temperatures are below 5°C or above 35°C.
- Fresh cementitious substrates such as site mix sand and cement render or concrete must be left for up to 28 days to sufficiently cure and contain no more than 15% WME prior to application.

Application

- To ensure colour consistency, the same paint batch should be used on the finish coat. If this is not possible then multiple pails should be boxed together.
- Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions. See ROCKCOTE's Technical Article on "Cutting In and avoiding picture framing".
- It is best practice to finish at an external or internal corner, or at a control line when work will continue the next day.
- Keep sheltered from rain and moisture for 24-48 hours after completion dependent on climatic conditions.
- For a textured stipple effect use a fine or medium texture roller sleeve.
- Applicator must check colour prior to application. ROCKCOTE will not accept liability once product has been applied.

Precautions and Limitations

- Should not be applied in temperatures below 5°C or above 35°C.
- Not suitable for areas of continual damp or areas submerged in water.
- Not suitable for floors.

Transport and Storage

- Store in a cool dark place.
- Keep pail sealed.
- Do not stack over 3 high.

Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

Technical Data Sheet

ROCKCOTE SOFFIT STIPPLE COAT

Effective From	01 Jan, 2019
-----------------------	--------------

Safety Data

Refer to ROCKCOTE Soffit Stipple Coat SDS

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.