

# TECHNICAL DATA SHEET

## ROCKCOTE TEXPRIME

Last Updated May 2014

**Description** ROCKCOTE Texprime is designed as a highly adhesive primer for all substrates that require a sand based primer. Its limited slip properties make it suitable for use on fibre cement sheeting, tilt-up and other smooth surfaces. Tilt up panels must be primed with ROCKCOTE Solprime before the application of ROCKCOTE Texprime. ROCKCOTE Texprime can be tinted to a wide range of colours, and is ideal as a primer for use with ROCKCOTE coloured renders and textures

### Features

- 10 year warranty\*
- Alkali Resistant
- Easy to use
- Highly adhesive

### Benefits

- Limited slip properties
- Reduces Suction
- Can be tinted
- Low roller spatter

**Uses**

- Reduces suction on porous and high suction substrates such as A.A.C. and cement sheeting
- Ideal for priming or sealing substrates prior to the application of ROCKCOTE Acrylic Coloured Render and Roll On Texture Systems
- Due to its unique anti slip qualities is ideal for applying over smooth surfaces prior to application of ROCKCOTE Trowel On Coloured Renders or base coats
- Can be used interior and exterior

**Colours and Gloss** Can be tinted to a wide range of colours

**Sheen Level** Matt

### Typical Data at 25 °C and 50% Relative Humidity

**Thinning** 5%

**Coverage Rate** Approximately 6 square metres per litre, Figures are a guide only. Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

**Drying Time** 4 hours

**Touch Dry** 2 hours

**Dry to Recoat** 4 hours

**Abrasion Resistance** Excellent

**Usual No Coats** 1

**Packaging Sizes** 15 Ltr & 4 Ltr pails

**Clean Up** Water

**Substrate Conditions**

- Surfaces should be clean, dry and free from loose or crumbling material, oil or form release agents
- Care should be taken to keep ROCKCOTE Primers off windows and adjacent surfaces that are not to be treated, as they can be very difficult to remove once allowed to dry
- All substrates must be installed as per manufacturers' specifications prior to application
- Not suitable for areas that will be submerged in water or subjected to continual moisture

**Flooring Installation** N/A

**Mixing** N/A

**Application**

- Check colour before use
- If using multiple pails on a wall, box drums prior to use
- The application of this product is a specialist procedure which should be carried out by a skilled and experienced applicator
- All substrates must contain no more than 15% WME before the application can commence
- It is important to maintain a wet edge when applying to avoid tracking and picture framing. [See ROCKCOTEs article on Picture Framing]
- Must be applied evenly and consistently to provide colour consistency and opacity for top coats

# TECHNICAL DATA SHEET

## ROCKCOTE TEXPRIME

Last Updated May 2014

- Can be applied with a quality brush or 15-20mm long nap sheepskin roller
- For tilt up precast concrete Panels, ROCKCOTE Solprime must be applied prior application of this product

### Safety Data

Refer to ROCKCOTE Texprime SDS

### Precautions and Limitations

- Should not be applied in air and surface temperatures below 5°C or above 35°C
- Should not be applied over glossy silicone based paints or sealants
- ROCKCOTE Primers should only be used over sound clean substrates, and are not suitable for areas that will be submerged in water or subjected to continual moisture
- ROCKCOTE Primers must only be used on substrates with a moisture level of less than 15% WME
- ROCKCOTE Primers are not suitable for use direct to substrate below damp proof installments

### Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 3 high

### Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

### Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

\* WHEN USED AS PART OF A FULL ROCKCOTE SYSTEM.