

TECHNICAL DATA SHEET

ROCKCOTE Tile Roof Primer

Last Updated March 2017

Description	ROCKCOTE Tile Roof Primer is a durable, flexible acrylic primer, designed for use on cement roof tiles. ROCKCOTE Tile Roof Primer is ideal for reducing suction of cement roof tile substrates and provides fantastic adhesion for top coats. The light base formulation provides great opacity and colour coverage for the final finish coat, particularly when changing dramatically between colours.	
	Features <ul style="list-style-type: none">• 12 year warranty*• Alkali resistant• Easy to use• Highly adhesive	Benefits <ul style="list-style-type: none">• Reduces suction• Provides great colour consistency
Uses	<ul style="list-style-type: none">• Ideal for highly porous concrete tiles, mildly porous concrete tiles and non porous concrete tiles• Ideal for priming and sealing cement tiles prior to the application of ROCKCOTE Solar Protect	
Colours and Gloss	Can be tinted to a wide range of colours	
Sheen Level	Low Sheen	

Typical Data at 25 °C and 50% Relative Humidity

Thinning	5%
Coverage Rate	Approximately 6 square metres per litre, Figures are a guide only. Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.
Drying Time	2 hours
Touch Dry	1 hours
Dry to Recoat	2 hours
Abrasion Resistance	Excellent
Usual No Coats	1
Packaging Sizes	15 Ltr pails
Clean Up	Water

Substrate Conditions	<ul style="list-style-type: none">• Surfaces should be clean, dry and free from loose or crumbling material, oil or form release agents• Care should be taken to keep ROCKCOTE Tile Roof Primer off adjacent surfaces that are not to be coated, as they can be very difficult to remove once allowed to dry• All substrates must be installed as per manufacturers' specifications prior to application• Not suitable for areas that will be submerged in water or subjected to water pooling• Replace any loose or damaged tiles and re point as necessary• Remove and dirt, mould, lichen and efflorescence prior to application• If necessary, treat the roof with ROCKCOTE Fungicidal Wash prior to application• If the surface still contains traces of efflorescence and chalking after thoroughly scuffing, cleaning and pressure washing, please contact the ROCKCOTE Technical Department
-----------------------------	--

Mixing	N/A
---------------	-----

Application	<ul style="list-style-type: none">• The application of this product is a specialist procedure which should be carried out by a skilled and experienced applicator• substrates must not contain more than 15% WME before application can commence• Should not be applied in temperatures below 10°C or above 35°C• Work in shaded areas wherever possible and follow the path of the sun as you work• When using an airless spray gun, a 517 tip size is recommended and apply at a maximum pressure of 3000 psi• ROCKCOTE Tile Roof Primer can be applied with a good quality brush (refer to coverage rate)
--------------------	---

Safety Data	Refer to ROCKCOTE Tile Roof Primer SDS
--------------------	--

TECHNICAL DATA SHEET

ROCKCOTE Tile Roof Primer

Last Updated March 2017

Precautions and Limitations

• Should not be applied in air and surface temperatures below 10°C or above 35°C • Should not be applied over glossy silicone based paints or sealants • ROCKCOTE Primers should only be used over sound clean substrates • ROCKCOTE Tile Roof Primer must only be used on substrates with a moisture level of less than 15% WME • ROCKCOTE Primers are not suitable for use direct to substrate below damp proof installments

Transport and Storage

• Store in a cool dark place • Keep pail sealed • Do not stack over 3 high

Disposal

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

* WHEN USED AS PART OF A FULL ROCKCOTE SYSTEM.